## (19) World Intellectual Property Organization International Bureau



## 

(43) International Publication Date 27 January 2005 (27.01.2005)

## (10) International Publication Number

(51) International Patent Classification7:

WO 2005/008701 A1

(21) International Application Number:

PCT/JP2004/010526

H01G 9/04

(22) International Filing Date:

16 July 2004 (16.07.2004)

(25) Filing Language:

English

(26) Publication Language:

**English** 

(30) Priority Data:

2003-199201 60/489,910

18 July 2003 (18.07.2003) JP 25 July 2003 (25.07.2003) US

- (71) Applicant (for all designated States except US): SHOWA DENKO K.K. [JP/JP]; 13-9, Shiba Daimon 1-chome, Mi-

- (74) Agent: OHIE, Kunihisa; Ohie Patent Office. Sclva-Ningyosho 6F, 14-6, Nihonbashi-Ningyocho, 2-chome, Chuo-Ku, Tokyo 103-0013 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

electric layer, and an electrically conducting layer stacked on the semiconductor layer, and the solid electrolytic capacitor element is molded with a resin, cured and then applied voltage (aging) treatment, which method comprises sequentially repeating a step of leaving the resin-molded body to stand at 225 to 305°C and a step of aging it twice or more after the steps of molding with resin and curing.